

# GYS DUST PRO 2 EXTRACTOR

Ref. 088535

Ref. 091436 | Complete with All Optional Accessories

INNOVATIVE  
CRTE



Heavy-Duty  
Pneumatic Dust  
Vacuum System

## Pneumatic Dust Extraction System for Professional Body Shops

The GYSDUST EXTRACTOR PRO 2 is a high-performance pneumatic vacuum extraction system designed for efficient sanding dust removal in automotive repair workshops. With dual connection ports, it allows connection of either two sanders or a sander and a vacuum block for added flexibility. Its patented automatic filter cleaning system eliminates manual maintenance, while full ATEX certification ensures safe operation during aluminum body repair.

### Two independent connection points:

Save time and increase efficiency by connecting two tools simultaneously for greater efficiency.

Supplied without sander or block. (088535)

Supplied with both on Complete (091436)

**Large 20L storage capacity:** Carry and store up to 10 boxes of sanding discs.



**Supplied with a collection bag.**

**Supplied with two hoses, 4 metres - ø 29 mm.**

### Side storage compartments x2:

Additional storage space for cleaning spray and sanding discs.

**Ergonomic twisted earth cable, 2.5m.**

For ground connection (ATEX requirement).

### Manual or AUTO position, patented automatic start system.

iAUTO mode only works with a motorised tool (sander). Each lever is independent.

### Automatic maintenance:

No maintenance required, with a patented automatic cleaning system on the suction unit.



**Regulator**

**Compressed air connection for blow-guns, air-powered screwdrivers, etc.**



**ATEX Category**  
Group II - Category 3



## OPTIONS

## FEATURES



**GYS brand**  
Pneumatic orbital sander —  
Eccentric 5mm D.150mm  
ref. 087897



**MIRKA brand**  
MIRKA PROS 650CV  
pneumatic sander  
ref. 071346



**Vacuum sanding block**  
ref. 089082



**Flexible vacuum sanding block**  
ref. 089099



**5 dust bags**  
ref. 058880

Bag capacity Air  
flow Air  
consumption  
Pressure Noise  
level Weight

7 kg 650 l/min  
250 l/min 1  
300 mm H2O  
70 dB (A)  
21 kg



PRODUCT PAGE

SALES  
SERVICE  
SUPPORT

(973) 768-9812  
WWW.INNOVATIVECRTE.COM

The pneumatic random orbital sander features a high-precision motor that delivers stable, consistent sanding performance — even under high pressure in demanding environments. Its efficient dust extraction system reduces airborne particles by up to 60% for a cleaner workspace. Designed with a low center of gravity and a perfectly balanced sanding pad, it provides exceptional control and comfort, making it ideal for extended use.

## ADVANTAGES

- Delivers high sanding performance with no backward rotation — even under pressure exceeding 30 kg.
- Up to 60% dust extraction efficiency for a significantly cleaner work environment.
- Powerful, lightweight, and perfectly balanced for durability and consistent workshop performance.



## WHAT'S INCLUDED

- Pneumatic random orbital sander
- Quick coupling
- Ø 150 mm sanding disc (pre-mounted)
- Service wrench



PRODUCT PAGE

Sanding pad size 6"	Noise emission		Vibration level	Air inlet	Air pressure (bar)	Dimensions (cm)	Weight (kg)
	L <sub>PA</sub>	L <sub>WA</sub>					
152 mm	81	92 dB (A)	12.2 (m/s <sup>2</sup> )	1/4"	6.3	63 x 28 x 33	1.4