# HANDERNINA.




# **Features**

Fast Work Cycles
High-Capacity 18V 4AH DC Battery
Meets OEM Specifications\*
Precise Pressure Adjustments
Produces Up to 55KN of Force
Pressure Adjustment Knob
Quick Arm Change
Quiet Operation
Rapid Battery Charging

# **Applications**

Self Piercing Rivets (SPR)
Solid Rivets
Rivet Removal
Flow Form Rivets
Calibrating Punch
Flattening
Pin & Collar





# About the CH-SPR-5

# Arms



### Fast Lock Plug Lock arm and fast connection shaft easily.

### Pressure Adjust Knob Adjust pressure according

to work demand.



SPR-40



### Trigger

Press to turn on the power and start operation, release to stop operation.

Pressure Release Button

Press to release pressure of cylinder and reset the extension bar.



SPR-130 (Optional)

## Multiple Arms

3 arm sizes available.

### Rechargeable Battery

18V rechargeable litihium battery.



# Specifi cations

25-55KN adjustable **Output Force** 

±3% Pressure Accuracy

Work Stroke 35~40mm Work Cycle 5-8 seconds

18V DC Motor Voltage

DC 18V 4AH lithium battery **Battery** 

AC 100V-240V 50-60Hz Charger Approximately 1 hour Charging Time

14°-104°F Work Temperatures

Work Time From Full Charge 130~350 times

(varies according to working pressure)

75db Noise





Post-style dies for longevity and ease-of-use.

# SPR-220 (Optional) Included Items

81mm

SPR-5 SPR-40 Arm Dies kit and toolbox Battery Charger (1) 18V Rechargeable Battery

Strap Case





SALES@INNOVATIVECRTE.COM

